

CUBE4-WET

Project Name:	
Type:	



CASAMBI

APPLICATION

The CUBE4-WET, wet location approved for covered ceilings, is a line of extruded aluminum linear luminaire suitable for multiple applications such as portico and front driveway of commercial, general office, banking, retail and educational environments.

FEATURES:

- Die-Cast and extruded aluminum housing, available in direct only and direct/indirect housing.
- Housing is fully gasketed and sealed.
- Standard powder-coat textured white painted finish.
- Comes with snap-in UV resistant polycarbonate lens.
- 360° rotatable luminaire (field adjustable) only available for pendant mount.
- High temperature silicone gasket.

MOUNTING:

- Pendant (1/2" stem pipe) mount, pipe provided by others.
- Wall mount.
- Surface mount (direct only).

LED:


- High quality array LEDs.
- LM80
- Color Temperature: 2700/3000/3500/4000/5000 (K)
- Color Rendering Index: > 80 (optional>90).
- Nominal Lamp Life: 100,000 hours.
- Reported L70 hours: +60,000 (55°C).

ELECTRICAL:

- High power factor electronic driver, operate from a 120~277 Vac input range, 50 / 60 Hz.
- Features included over voltage protection, surge, short circuit protection and over load protection.
- Power Factor: typical > 0.95, THD <20, meets Class1 or Class 2 circuit.
- 0-10VDC, 1%~100% dimmable driver as standard.
- Operating temperature: -4°F (-20°C) ~ 122°F (50°C).
 - **UL listed for wet location for covered ceilings.** <ELCU-200>
- Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
- Interfaces with fire alarm panel or security system.
- "Watchdog" feature allows emergency loads to be controlled in tandem with normal power loads.
- UL listed for use in emergency circuits.


LISTING:

- ROHS.
- UL /cUL listed.
- Listed to UL 1598 and UL 8750.
- UL listed for wet location for covered ceilings.
- UL listed for outdoor wet location for non-covered ceiling (select OL option)
- CEC Compliant EM (please contact for more information).
- BAA compliant (optional).
- Trade Agreements Act compliant (optional).
- 5 years limited warranty.
- 7 or 10 years limited warranty (optional).¹²



Specifications: CUBE4-WET (down only)

Width: 4 (101.6)
Depth: 4.5 (114.3)



Specifications: CUBE4-WET (up & down)

Width: 4 (101.6)
Depth: 4.5 (114.3)

All dimensions are in inches (millimeters).

CUBE4-WET

CONFIGURATIONS

Series	Size	Model #	AC Input	Lumen Output (Down)		Lumen Efficiency
CUBE4-WET	2'	18L	9.9W	1209.58 lm (100%)	1209.58 lm	122.18 lm/W
		27L	14.85W	1868.7 lm (100%)	1868.7 lm	125.84 lm/W
		36L	19.8W	2482.1 lm (100%)	2482.1 lm	125.36 lm/W
		48L	26.4W	3073.65 lm (100%)	3073.65 lm	116.4 lm/W
		54L	29.7W	3507.57 lm (100%)	3507.57 lm	118.10 lm/W
	3'	18L	14.85W	1814.3 lm (100%)	1814.3 lm	122.18 lm/W
		27L	22.27W	2802.45 lm (100%)	2802.45 lm	125.84 lm/W
		36L	29.7W	3723.19 lm (100%)	3723.19 lm	125.36 lm/W
		48L	39.6W	4610.48 lm (100%)	4610.48 lm	116.4 lm/W
		54L	44.55W	5261.3 lm (100%)	5261.3 lm	118.10 lm/W
	4'	18L	19.8W	2419.2 lm (100%)	2419.2 lm	122.18 lm/W
		27L	29.7W	3737.5 lm (100%)	3737.5 lm	125.84 lm/W
		36L	39.6W	4964.4 lm (100%)	4964.4 lm	125.36 lm/W
		48L	52.8W	6147.4 lm (100%)	6147.4 lm	116.4 lm/W
		54L	59.4W	7015.7 lm (100%)	7015.7 lm	118.10 lm/W
	6'	18L	29.7W	3628.7 lm (100%)	3628.7 lm	122.18 lm/W
		27L	44.55W	5606.1 lm (100%)	5606.1 lm	125.84 lm/W
		36L	59.4W	7446.38 lm (100%)	7446.38 lm	125.36 lm/W
		48L	79.2W	9220.96 lm (100%)	9220.96 lm	116.4 lm/W
		54L	89.1W	10522.71 lm (100%)	10522.71 lm	118.10 lm/W
	8'	18L	39.6W	4838.3 lm (100%)	4838.3 lm	122.18 lm/W
		27L	59.4W	7474.89 lm (100%)	7474.89 lm	125.84 lm/W
		36L	79.2W	9928.5 lm (100%)	9928.5 lm	125.36 lm/W
		48L	105.6W	12294.6 lm (100%)	12294.6 lm	116.4 lm/W
54L		118.8W	14030.28 lm (100%)	14030.28 lm	118.10 lm/W	

CCT	Multiplier		
	3000K	3500K	5000K
Down only	0.983631	0.991815	1.016369
Up&Down	0.988745	0.994373	1.011255

CUBE4-WET

CONFIGURATIONS

Series	Size	Model #	AC Input	Lumen Output (Down)	Lumen Efficiency
CUBE4-WET	2'	18L/18L	19.8W	1184.4 lm (49.4% Down) / 1213.9 lm (50.6% Up)	2398.95 lm 121.15 lm/W
		27L/18L	24.75W	1870.87 lm (60.6% Down) / 1216.38 lm (39.4% Up)	3087.25 lm 124.73 lm/W
		27L/27L	29.7W	1863.6 lm (51.1% Down) / 1783.35 lm (48.9% Up)	3646.95 lm 122.79 lm/W
		36L/18L	29.7W	2312.1 lm (66.1% Down) / 1185.9 lm (33.9% Up)	3498 lm 117.77 lm/W
		36L/27L	34.65W	2492.9 lm (57.7% Down) / 1827.7 lm (42.3% Up)	4320.6 lm 124.69 lm/W
		48L/18L	36.3W	2850.1 lm (70.5% Down) / 1192.7 lm (29.5% Up)	4042.8 lm 111.37 lm/W
		48L/27L	41.25W	3029.2 lm (62.9% Down) / 1786.7 lm (37.1% Up)	4815.9 lm 121.15 lm/W
		54L/18L	39.6W	3316.68 lm (73.5% Down) / 1195.82 lm (26.5% Up)	4512.5 lm 113.9 lm/W
	54L/27L	44.55W	3468 lm (66.1% Down) / 1778.65 lm (33.9% Up)	5246.65 lm 117.77 lm/W	
	3'	18L/18L	29.7W	1776.7 lm (49.4% Down) / 1820.9 lm (50.6% Up)	3598.4 lm 121.15 lm/W
		27L/18L	37.12W	2806.3 lm (60.6% Down) / 1824.57 lm (39.4% Up)	4630.87 lm 124.73 lm/W
		27L/27L	44.55W	2795.3 lm (51.1% Down) / 2675.1 lm (48.9% Up)	5470.4 lm 122.79 lm/W
		36L/18L	44.55W	3468.2 lm (66.1% Down) / 1778.8 lm (33.9% Up)	5247 lm 117.77 lm/W
		36L/27L	51.97W	3739.4 lm (57.7% Down) / 2741.5 lm (42.3% Up)	6480.9 lm 124.69 lm/W
		48L/18L	54.45W	4275.3 lm (70.5% Down) / 1788.95 lm (29.5% Up)	6064.25 lm 111.37 lm/W
		48L/27L	61.8W	4543.8 lm (62.9% Down) / 2680.05 lm (37.1% Up)	7223.85 lm 121.15 lm/W
		54L/18L	59.4W	4975 lm (73.5% Down) / 1793.75 lm (26.5% Up)	6768.75 lm 113.9 lm/W
	54L/27L	66.82W	5201.66 lm (66.1% Down) / 2667.73 lm (33.9% Up)	7869.39 lm 117.77 lm/W	
	4'	18L/18L	39.6W	2368.9 lm (49.4% Down) / 2427.9 lm (50.6% Up)	4797.9 lm 121.15 lm/W
		27L/18L	49.5W	3741.7 lm (60.6% Down) / 2432.8 lm (39.4% Up)	6174.5 lm 124.73 lm/W
		27L/27L	59.4W	3727.18 lm (51.1% Down) / 3566.72 lm (48.9% Up)	7293.9 lm 122.79 lm/W
		36L/18L	59.4W	4624.4 lm (66.1% Down) / 2371.7 lm (33.9% Up)	6996.1 lm 117.77 lm/W
		36L/27L	69.3W	4985.9 lm (57.7% Down) / 3655.3 lm (42.3% Up)	8641.2 lm 124.69 lm/W
		48L/18L	72.6W	5700.4 lm (70.5% Down) / 2385.27 lm (29.5% Up)	8085.67 lm 111.37 lm/W
		48L/27L	82.5W	6058.4 lm (62.9% Down) / 3573.4 lm (37.1% Up)	9631.8 lm 121.15 lm/W
		54L/18L	79.2W	6633.3 lm (73.5% Down) / 2391.7 lm (26.5% Up)	9025 lm 113.9 lm/W
	54L/27L	89.1W	6936 lm (66.1% Down) / 3557.3 lm (33.9% Up)	10493.30 lm 117.77 lm/W	
	6'	18L/18L	59.4W	3553.4 lm (49.4% Down) / 3641.9 lm (50.6% Up)	7196.85 lm 121.15 lm/W
		27L/18L	74.25W	5612.6 lm (60.6% Down) / 3649.15 lm (39.4% Up)	9261.75 lm 124.73 lm/W
		27L/27L	89.1W	5590.77 lm (51.1% Down) / 5350.08 lm (48.9% Up)	10940.85 lm 122.79 lm/W
		36L/18L	89.1W	6936.6 lm (66.1% Down) / 3557.55 lm (33.9% Up)	10494.15 lm 117.77 lm/W
		36L/27L	103.9W	7478.95 lm (57.7% Down) / 5482.85 lm (42.3% Up)	12961.8 lm 124.69 lm/W
		48L/18L	108.9W	8550.6 lm (70.5% Down) / 3577.9 lm (29.5% Up)	12128.5 lm 111.37 lm/W
		48L/27L	123.75W	9087.6 lm (62.9% Down) / 5360.1 lm (37.1% Up)	14447.7 lm 121.15 lm/W
		54L/18L	118.8W	9950 lm (73.5% Down) / 3587.5 lm (26.5% Up)	13537.5 lm 113.9 lm/W
	54L/27L	133.65W	10404.11 lm (66.1% Down) / 5335.85 lm (33.9% Up)	15739.96 lm 117.77 lm/W	
	8'	18L/18L	79.2W	4737.9 lm (49.4% Down) / 4855.9 lm (50.6% Up)	9595.8 lm 121.15 lm/W
		27L/18L	99W	7483.5 lm (60.6% Down) / 4865.5 lm (39.4% Up)	12349 lm 124.73 lm/W
		27L/27L	118.8W	7454.3 lm (51.1% Down) / 7133.5 lm (48.9% Up)	14587.8 lm 122.79 lm/W
		36L/18L	118.8W	9248.8 lm (66.1% Down) / 4743.4 lm (33.9% Up)	13992.2 lm 117.77 lm/W
		36L/27L	138.6W	9971.9 lm (57.7% Down) / 7310.5 lm (42.3% Up)	17282.4 lm 124.69 lm/W
		48L/18L	145.2W	11400.8 lm (70.5% Down) / 4770.54 lm (29.5% Up)	16171.34 lm 111.37 lm/W
		48L/27L	165W	12116.8 lm (62.9% Down) / 7146.8 lm (37.1% Up)	19263.6 lm 121.15 lm/W
		54L/18L	158.4W	13226.75 lm (73.5% Down) / 4783.25 lm (26.5% Up)	18050 lm 113.9 lm/W
	54L/27L	178.2W	13872.15 lm (66.1% Down) / 7114.46 lm (33.9% Up)	20986.61 lm 117.77 lm/W	

CCT	Multiplier		
	3000K	3500K	5000K
Down only	0.983631	0.991815	1.016369
Up&Down	0.988745	0.994373	1.011255

ARCHITECTURAL WET LOCATION LINEAR

ORDERING INFORMATION

EXAMPLE: CUBE4-IND-WET-4-D27L/U18L-30K-UNV

MODEL	WET		ROW ¹		SECTION ²		LED Downlight (per/4ft section)		LED Uplight (per/4ft section)	
CUBE4-IND (Individual Mount) CUBE4-CON (Continuous Row Mount)	WET	Wet Location	xx'	Specify nominal overall row length in 1' increments (Continuous runs)	2	2' Length	D18L	18W LED (725 lm/ft)	(Blank)	No Uplight
					3	3' Length	D27L	27W LED (1172 lm/ft)	/U18L	18W LED (683 lm/ft)
					4	4' Length	D36L	36W LED (1241 lm/ft)	/U27L	27W LED (976 lm/ft)
					6	6' Length	D48L	48W LED (1536 lm/ft)		
					8	8' Length	D54L	54W LED (1753 lm/ft)		
* Number of circuit(s) should be determined by the customer prior to ordering the continuous run considering the AC input voltage and total run wattage.					* Maximum wattage per 4ft section - pendant/wall mount : 75W(up & down light) * Contact factory for custom wattage or lumen requirement.					

Downlight DISTRIBUTION		Uplight DISTRIBUTION		COLOR TEMP.		SEPARATE CCT.		CRI	
(Blank)	Standard Wall wash	(Blank)	Standard Lens	(Blank)	Leave blank if you wish to have different CCT for up and down, and fill out next section	(Blank)	Leave blank if you chose to have the same CCT for up and down in the previous section	(Blank)	80+ CRI
WW		UN15	Uplight Narrow 15°	-27K	2700K ³	DXXUYY	Indicate 27,30,35,40, or 50 for XX and YY (D represents Downlight, U represents Uplight)	C9	90+ CRI ⁴
		UN30	Uplight Narrow 30°	-30K	3000K				
		UM	Uplight Medium 60°	-35K	3500K				
		UASY	Uplight Asymmetric 20° ¹⁴	-40K	4000K				
		UBAT	Uplight Batwing 120°	-50K	5000K				

VOLTAGE		EM SECTION ⁶		HOUSING FINISH		CANOPY FINISH		MOUNTING	
UNV	120-277V	(Blank)	None EM	(Blank)	Matte White RAL #9003 (Std.)	(Blank)	White (Std.)	X1-ST24	15/16" grid T-bar + 24" Stem
120	120V	1SE	1 Section	*BK	Black RAL #9011	*BC	Black Canopy	X1-ST48	15/16" grid T-bar + 48" Stem
277	277V	2SE	2 Section	*SV	Silver (RAL #9022)	*SC	Silver Canopy	X2-ST24	Drywall + 24" Stem
347	347V ⁵	xSE	x Section	**CC	Custom Color ⁷	**CSS	Custom Canopy Color	X2-ST48	Drywall + 48" Stem
				*AMB	Anti-Microbial Coating (Matte Skye White)			X3-ST24	Sloped drywall + 24" Stem
								X3-ST48	Sloped drywall + 48" Stem
								X4-ST24	9/16" grid T-bar + 24" Stem
								X4-ST48	9/16" grid T-bar + 48" Stem
								S	Ceiling Surface
								W	Wall
									* Contact factory for custom length.
									* 1 pair stem and canopy kits standard for up to 8ft length.

LED DRIVER		OPTIONS	
(Blank)	0-10V dim to 1% (Std.) (dim both uplight and downlight simultaneously)	OL	UL listed for outdoor wet location for non-covered ceiling
UDSD	Separate Dimming Control of Uplight and Downlight (0-10V dim to 1%) ^{8,9}	EMG8	8W EM Battery Backup (CEC Compliant EM) ¹⁰
SP	Separate Power Control for Uplight and Downlight	EMG15	15W EM Battery Backup (CEC Compliant EM) ¹⁰
ES566	eldoLED SOLODrive Natural Dimming to dark, 0-10V, 100% ~ 0.1% dim	EMG20	20W EM Battery Backup (CEC Compliant EM) ¹⁰
SD40	40% / 100% Bi-Level Step dim	ELCU-200	Fail-to-on Emergency lighting, UL924 ¹¹
SDXX	XX% / 100% Bi-Level Step dim (Specify XX : 10% ~ 70%)	GTD	Bodine Generator Transfer Device
PHSR	Philips Xitanium Sensor-Ready, DALI 5%~100% dim.	GTD10DIM	Bodine Generator Transfer Device (0-10VDC Dimmer Override)
PHDL	Philips Xitanium DALI driver, Dim to 5%	F1	Single fuse for 120/277/347V ¹³
EC	eldoLED ECOdrive 0-10V natural dim to 1% (Hybrid HydraDrive)	F2	Double fuse for 208/240V ¹³
TDM	Triac Dim. (120V only)	LT	Low Temperature (-40°F (-40°C) ~ 122°F (50°C))
TD30/70	30% / 70% / 100% Tri-Level Step dim	O7W	Optional 7 Years Limited Warranty ¹²
TDXX/YY	XX% / YY% / 100% Tri-Level Step dim(Specify XX, YY : 10%~70%)	O10W	Optional 10 Years Limited Warranty ¹²
LDE1	Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology, 100% ~ 1% dim	COC	Separated EM feed for City of Chicago code compliance
ELV	ELV compatible (reverse-phase or trailing-edge)	BAA	BAA(Buy American Act) and BABA(Build America Buy America) compliant
DT0	0-10V DIM-TO-OFF	TAA	Trade Agreements Act compliant
DIMT	Tri-mode dimming (Triac, ELV, 0-10V)	MG	Marine grade finish
LTEA2W	Hi-lume 1% 2-wire LED driver (120V forward phase only) ³⁰	E1F	End feed on one end (Pre-drilled hole for 1/2" fitting)
		E2F	End feed on both ends (Pre-drilled holes for 1/2" fitting)
		SP10	10KV/10KA integrated surge protection
		HC403	Hytronik Daylight Harvesting Occupancy Sensor, adjustable via DIP switch ¹⁵
		CASAMBI	Contact factory for CASAMBI READY options

NOTES:

- Specify only when continuous row mount.
- Skip if the row length and section length are the same.
- Available with C9 (CRI 90+) only.
- Lumen per watt is around 15% less than standard CRI 80+.
- 347V cannot work with emergency battery backup.
- EM is installed in the last 4' of luminaire section. Separate section required 2SE or specified. Must specify voltage, not available with 347V.
- Refer to color charts (RAL / Cardinal) in the separate attachment.
- UDSD option with EM may not be available due to limited space, please contact us for more information.
- Built with up to 2 power feeds depending on the configuration.
- Contact factory for other emergency battery backup options.
- Shipped separately.
- This limited warranty covers electrical parts only and does not apply to labor, equipment lease, or defect from improper installation or operation.
- Must specify voltage.
- Standard optic illuminates the wall. Optics can be field modified (reversed) to illuminate room.
- See Table 2 to find factory setting.


CUBE4-WET



Up & Down with pendant mount




Down only with pendant mount



Surface & Wall mount


MOUNTING DETAILS

- PENDANT MOUNT (shown in direct/indirect housing)



All dimensions are in inches (millimeters).

- WALL MOUNT



CUBE4-WET

COMPATIBLE DIMMER SWITCH (TABLE 1)

Model #	Brand	Compatible Dimmer Switch	
(Blank)	-	<Leviton>	IlumaTech IP7 series
		<Lutron>	Visit www.lutron.com/advance for a list of dimmers (Mark VII) that will work with this driver.
		<Philips>	Sunrise : SR1200ZTUNV
ES566	eldoLED SOLOdrive	<Busch-Jaeger>	2112U-101
		<Jung>	240-10
		<Leviton>	IlumaTech - IP710-DLX
		<Lightoller Controls>	ZP600FAM120
		<Merten>	5729
		<Pass & Seymour>	CD4FB-W
		<Wattstopper>	DCLV1
		<Sensor Switch>	nIO EZ
		<Synergy>	ISD BC
		<ABB>	SD/S 2.16.1
		<Lutron>	Nova T: NTFTV Diva - DDTV-xx, NFTV GRAFIK Eye: GRX-TVI w GRX3503 Energy Savr Node: QSN-4T16-S TVM2 Module
		<Crestron>	GLX-DIMFLV8, GLXP-DIMFLV8, GLPAC-DIMFLV4-*, GLPAC-DIMFLV8-*, GLPP-DIMFLVEX-PM, GLPP-1DIMFLV2EX-PM, GLPP-1DIMFLV3EX-PM, DIN-AO8, DIN-4DIMFLV4, CLS-EXP-DIMFLV, CLCI-1DIMFLV2EX
LDE1	Lutron Hi-lume 1% EcoSystem	<Lutron>	PowPak Dimming Modules: RMJ-ECO32-DV-B, FCJ/FCJS-ECO ^{1,2} Energi Savr Node (120V only): QSN-1ECO-S, QSN-2ECO-S GRAFIK Eye QS/Homeworks QS control unit (120V only): QSGRJ-_E(wireless) QSGR-_E Quantum Hub (120V only): QP2-__2C/4C/6C/8C Homeworks QS/myRoom Plus power module (120V only): LQSE-2ECO-D
PHSR ³	Philips Xitanium Sensor-Ready	<Ilumra>	<u>Single Rocker Self-Powered Light Switch (on/off, dim-up/down)</u> Ilumra# ZBT-S1AWH Digi-Key# 1082-1033-ND <u>Dual Rocker Self-Powered Light Switch (on/off, dim-up/down, scene1,2)</u> Ilumra# ZBT-S2AWH Digi-Key# 1082-1034-ND
TDM	KEYSTONE	<Lutron>	Diva DV-600P, SkyLark S-600P, Maestro MA-600 (Digital)
ELV	ERP	<Lutron>	Nova-NFTV, Diva-DDTV
DTO	Philips Xitanium Gen.2 Philips Xitanium Sensor-Ready	<Lutron>	Nova T: #NTSTV-DV http://www.lutron.com/TechnicalDocumentLibrary/NovaTB.pdf See page13.
LTEA2W	Lutron Hi-lume 2-wire (120V forward voltage only)	<Lutron>	Visit http://www.lutron.com/TechnicalDocumentLibrary/369543_ENG.pdf for a list of compatible dimmer switches.

NOTES:

- All devices connected to one FCJ/FCJS-ECO will be controlled together. Devices will dim to the same level as the result of a control command. For more detail on adjusting low-end light level refer to Application Note#556 at www.lutron.com.
- For the Line/Hot (L/H) terminal on the driver, it is preferred not to use the switched hot (red) wire from the control but rather the hot wire directly from the power source.
- Recommended for EasySense System.

HC403 FACTORY SETTING (TABLE 2)

Detection Area	100%
Hold-time	5 sec
Daylight sensor	Disable
Stand-by period (tri-level control)	10 sec
Stand-by dimming level	10%

* See a separate attachment to find more setting options.