

CUBE2-NRC-X

Project Name:	
Type:	



APPLICATION

The CUBE2-NRC offers an easy integration of lighting and acoustic solutions. While the acoustic provides an acoustic solution to the source of noise for optimal sound absorption, seamlessly designed acoustic felt gives design flexibility and personalization for any application. Perfect for places in need to reduce reverberation such as open offices and lobbies, retails, hospitality, reception areas and corridors, and commercial interiors.

FEATURE:

- Luminaire is available in 90 or 135 degree shape.
- Sound absorbing linear direct acoustic LED luminaire.
- Material rated for NRC (Noise Reduction Coefficient) of 0.90.
- Acoustic felt is 100% virgin polyester and 0.5" thick.
- 45 degree deburr design is standard. Flushed design is available upon request.
- Available in 6" to 24" nominal housing heights in 2" increments.
- Wide range of felt color (2 standards and 18 premium) options available. Refer to the last page for color offering.

MOUNTING:

- Pendant mount.
- Pendant Surface mount (optional).

LED:

- High quality array LEDs.
- LM80
- Color Temperature: 2700/3000/3500/4000/5000 (K).
- Color Rendering Index: >80 (optional>90).
- Nominal Lamp Life: 100,000 hours.
- Reported L70 hours: +60,000 (55°C).

ELECTRICAL:

- High power factor electronic driver, operate from a 120 ~ 277 Vac input range, 50 / 60 Hz.
- Features included over voltage protection, surge, short circuit protection and over load protection.
- Power Factor: typical > 0.95, THD <20, meets Class1 or Class 2 circuit.
- 0-10V dimmable driver as standard.
- 0-10VDC dimming 1%~100%.
- Operating temperature: -4°F (-20°C) ~ 122°F (50°C).

<ELCU-200>

- Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
- Interfaces with fire alarm panel or security system.
- "Watchdog" feature allows emergency loads to be controlled in tandem with normal power loads.
- UL listed for use in emergency circuits.

FINISH:

- Fixture is powder-coated in standard white finish.
- Comes with snap-in acrylic lens as standard.

LISTING:

- UL / CUL listed.
- Listed to UL 1598 and UL 8750.
- UL listed for dry & damp location.
- CEC Compliant EM (please contact for more information)
- Assembled in USA (optional).
- BAA compliant (optional).
- Trade Agreements Act compliant (optional).
- 5 years limited warranty.
- 7 or 10 years limited warranty. (optional) ⁶
- Bluetooth Mesh System available, please contact factory for more information.


CONFIGURATIONS

Series	Model #	AC Input	Fixture Lumen Output (4000K)		Lumen Efficiency (4000K)
CUBE2-X	18L	19.8W	2562.12 lm (100% Down)	2562.12 lm	129.40 lm/W
	27L	29.7W	3283.33 lm (100% Down)	3283.33 lm	110.55 lm/W
	36L	39.6W	4244.72 lm (100% Down)	4244.72 lm	107.19 lm/W
	48L	49.8W	5303.70 lm (100% Down)	5303.70 lm	106.5 lm/W
	54L	57W	5849 lm (100% Down)	5849 lm	105.96 lm/W

CCT	Multiplier		
	3000K	3500K	5000K
Down only	0.9642	0.9822	1.0357

OUTPUT CURRENT

		Bi-Level		Tri-Level (Default)	
SW1	SW2	Config Range	Default	Config Range	Default
Close	Open	10% - 70%	40%	10% - 70%	30%
Open	Close	10% - 70%	40%	10% - 70%	70%
Close	Close	100%	100%	100%	100%
Open	Open	0%	0%	0%	0%



Specifications: CUBE2-NRC


Width: 3.5 (88.9)
Depth: MIN.6 (152.4)

All dimensions are in inches (millimeters).

WEIGHT

Item	lbs	kg
CUBE2-X	15.08	6.84

CUBE2-NRC-X



AMS, IFS105SE coverage pattern

ORDERING INFORMATION

EXAMPLE: CUBE2-NRC-X-D27L-30K-UNV-X1-AC48

MODEL	SHAPE	HEIGHT (heights are nominal)	LED Downlight	COLOR TEMP.	CRI	MOUNTING
CUBE2-NRC	X X Shape	6 6" (Minimum) 8 8" 10 10" 12 12" XX Custom Height, Max. 24" (2" increments)	D18L 18W LED D27L 27W LED D36L 36W LED D54L 54W LED	-27K 2700K ¹ -30K 3000K -35K 3500K -40K 4000K -50K 5000K	(Blank) C9 80+ CRI 90+ CRI ²	(Blank) PS Pendant Pendant Surface
	CM Custom pattern (must provide a sketch on the last page of this spec sheet)		* Maximum wattage per 4ft section - 54W (down light) * Contact factory for custom wattage or lumen requirement.			


VOLTAGE	EM SECTION ⁴	FINISH (fixture)	FINISH (baffle)	CORD FINISH
UNV 120-277V 120 120V 277 277V 347 347V ³	(Blank) None EM 1SE 1 Section xSE x Section	(Blank) Matte White RAL #9003 (Std.) *BK Black RAL #9011 *SV Silver (Cardinal #T353-GR06) **CC Custom Color *AMB Anti-Microbial Coating (Matte Sky White) * Non-standard finish with extra charge. ** Additional charge & set up fee.	SL Slate PW Pewter CC Premium Color (choose 2 letters from the last page) * Contact factory for lead time and pricing for premium color.	(Blank) White (Std.) *BKC Black * Non-standard finish with extra charge. ** Additional charge & set up fee.

CANOPY FINISH	CEILING TYPE	SUSPENSION LENGTH	LED DRIVER
(Blank) White (Std.) *BC Black Canopy *SC Silver Canopy **CSS Custom Canopy Color (White is Std.) * Non-standard finish with extra charge. ** Additional charge & set up fee.	X1 T-bar ceiling X2 Hard ceiling X3 Sloped Hard ceiling X5 9/16" Screw Slot ceiling	AC48 Adjustable Aircraft Cable Canopy 48"L AC96 Adjustable Aircraft Cable Canopy 96"L ST24 Stem Canopy 24"L ST48 Stem Canopy 48"L * Contact factory for custom length. * add "FC" at the end of stem length for field cuttable stem kit (Ex) ST48FC)	(Blank) 0-10V dim to 1% (Std.) ES566 eldoLED SOLOdrive Natural Dimming to dark, 0-10V, 100% ~ 0.1% dim SD40 40% / 100% Bi-Level Step dim SDXX XX% / 100% Bi-Level Step dim (Specify XX : 10% ~ 70%) PHSR Philips Xitanium Sensor-Ready, Dali 5%~100% dim. PHDL Philips Xitanium DALI driver, Dim to 5% TDM Triac Dim. (120V only) TD30/70 30% / 70% / 100% Tri-Level Step dim TDXX/YY XX% / YY% / 100% Tri-Level Step dim (Specify XX, YY : 10% ~ 70%) LDE1 Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology, 100% ~ 1% dim ELV ELV compatible (reverse-phase or trailing-edge), (120V only) TRIOT Tridonic IoT ready, 1-100% dim via Smart Module Interface (SMI), automated dimming/lighting controls via Enlighted Sensor Interface DTO 0-10V DIM-TO-OFF LTEA2W Hi-lume 1% 2-wire LED driver (120V forward phase only) ¹⁵ BLT Bluetooth Mesh System (contact factory for more information)


OPTIONS		LIGHTING CONTROL SYSTEM	
EMG8	1296 LUMEN EM Battery Backup (CEC Compliant EM) ^{5,6}	LUTRON VIVE  Click Here! SNS200 EasySense Fixture-mount occupancy sensing, daylight harvesting and task tuning in one device (Must be ordered with PHSR driver) ^{12,13} RS-IR IR dongle v2.0 for EasySense control SU-5E Enlighted IoT ready 0-10V Indoor Micro sensor with occupancy/vacancy detection, daylight harvesting, thermal sensing, task tuning, and room and zone control, Bluetooth enabled (Must be ordered with TRIOT) ¹⁴ RS-WS Enlighted Room controller providing basic control functions of a standard wall switch with preset dimming capability IFS105SE Bluetooth Mesh Wireless Sensor. Occupancy/Daylight/0-10V Dimming PPA102S Bluetooth Powerpack (Consult factory for installation location) CASAMBI Contact factory for CASAMBI READY options	
EMG15	2430 LUMEN EM Battery Backup (CEC Compliant EM) ^{5,6}		
EMG20	3240 LUMEN EM Battery Backup (CEC Compliant EM) ^{5,6}		
EMG25	4050 LUMEN EM Battery Backup (CEC Compliant EM) ^{5,6}		
ELCU-200	Fail-to-on Emergency lighting, UL924 ⁷		
F1	Single Fuse for 120/277/347V ⁸		
F2	Double Fuse for 208/240V ⁸		
ARRA	Assembled in USA for Buy American Act		
BAA	BAA(Buy American Act) and BABA(Build America Buy America) compliant		
TAA	Trade Agreements Act compliant		
O7W	Optional 7 Years Limited Warranty ⁹		
O10W	Optional 10 Years Limited Warranty ⁹		
AMS	Bluetooth Mesh Wireless Sensor. Occupancy/Daylight/0-10V Dimming ¹⁶		
DPMS	Daylight Dimming Photo Sensor (0-10 VDC Control), (LSR-301-S required if FD-301 is installed) ¹¹		
SO	Dimming Wires connected to Sensor Only (available option on FS-205 non-Bluetooth AMS sensor only) ¹⁰		
LSR-301-S	Setup Remote Control for DPMS (Required for DPMS)		
LSR-301-P	Occupant Remote Control for DPMS		

NOTES:


- Available with C9 (CRI 90+) only.
- Lumen per watt is around 15% less than standard CRI (80+).
- 347V not available with Emergency Battery Backup.
- EM is installed in last 4' of luminaire sections. Separate section requires 2SE or specified.
- Contact factory for other emergency battery backup options.
- For individual piece order, remote EM is provided due to limited space.
- Shipped separately.
- Must provide voltage.
- This limited warranty covers electrical parts only and does not apply to labor, equipment lease, or defect from improper installation or operation.
- Dimming wires provided and connected to sensor only, not for dimmer switch.
- Automatic on/off is not available. For automatic on/off, additional occupancy sensor is required or a manual on/off switch can be done.
- See NFC and IR manual in the separate attachment. If your phone is not compatible, please order "RS-IR" and follow the manual.
- Refer to Advanced Grouping Datasheet for its default setting and compatible wireless switches.
- "RS-WS" option can be added if wish to have a wall switch, please see Enlighted Room Controller in the separate attachment.
- Not available with any 1ft individual configuration due to space limitations.
- With TDM/ELV/SDxx/TDxx: Only available with line-voltage on/off occupancy sensor.




All dimensions are in inches (millimeters).



Cable



Stem



COMPATIBLE DIMMER SWITCH (TABLE 1)


Model #	Brand	Compatible Dimmer Switch	
(Blank)	-	<Leviton>	IP710-LFZ
		<Lutron>	Visit www.lutron.com/advance for a list of dimmers (Mark VII) that will work with this driver.
ES566	eldoLED SOLOdrive	<Busch-Jaeger>	2112U-101
		<Jung>	240-10
		<Leviton>	IlumaTech - IP710-DLX
		<Lightoller Controls>	ZP600FAM120
		<Merten>	5729
		<Pass & Seymour>	CD4FB-W
		<Wattstopper>	DCLV1
		<Sensor Switch>	nIO EZ
		<Synergy>	ISD BC
		<ABB>	SD/S 2.16.1
		<Lutron>	Nova T: NTFTV Diva - DVTV-xx, NFTV GRAFIK Eye: GRX-TVI w GRX3503 Energy Savr Node: QSN-4T16-S TVM2 Module
		<Crestron>	GLX-DIMFLV8, GLXP-DIMFLV8, GLPAC-DIMFLV4-*, GLPAC-DIMFLV8-*, GLPP-DIMFLVEX-PM, GLPP-1DIMFLV2EX-PM, GLPP-1DIMFLV3EX-PM, DIN-AO8, DIN-4DIMFLV4, CLS-EXP-DIMFLV, CLCI-1DIMFLV2EX
LDE1	Lutron Hi-lume 1% EcoSystem	<Lutron>	PowPak Dimming Modules: RMJ-ECO32-DV-B, FCJ/FCJS-ECO ^{1,2} Energi Savr Node (120V only): QSN-1ECO-S, QSN-2ECO-S GRAFIK Eye QS/Homeworks QS control unit (120V only): QSGRJ- E(wireless) QSGR- E Quantum Hub (120V only): QP2- _2C/4C/6C/8C Homeworks QS/myRoom Plus power module (120V only): LQSE-2ECO-D
PHSR ³	Philips Xitanium Sensor-Ready	<Ilumra>	Single Rocker Self-Powered Light Switch (on/off, dim-up/down) Ilumra# ZBT-S1AWH Digi-Key# 1082-1033-ND Dual Rocker Self-Powered Light Switch (on/off, dim-up/down, scene1,2) Ilumra# ZBT-S2AWH Digi-Key# 1082-1034-ND
TDM	KEYSTONE	<Lutron>	Diva DV-600P, SkyLark S-600P, Ariadni AY-600P, Ariadni TG-603P, Maestro MA-600 (Digital), Diva CFL/LED DVCL-153P, Satin Colors DVSC-600P-SW
		<Leviton>	6641, IlumaTech IPI06-1LX, ToggleTouch TGI06-1LW (Digital)
ELV	KEYSTONE	<Lutron>	MAELV-600BL (Digital), DVELV-300P, SkyLark SELV-300P
DTO	Philips Xitanium Gen.2 Philips Xitanium Sensor-Ready	<Lutron>	Nova T: #NTSTV-DV http://www.lutron.com/TechnicalDocumentLibrary/NovaTB.pdf See page13.
LTEA2W	Lutron Hi-lume 2-wire (120V forward voltage only)	<Lutron>	Visit http://www.lutron.com/TechnicalDocumentLibrary/369543_ENG.pdf for a list of compatible dimmer switches.

NOTES:

- All devices connected to one FCJ/FCJS-ECO will be controlled together. Devices will dim to the same level as the result of a control command. For more detail on adjusting low-end light level refer to Application Note#556 at www.lutron.com.
- For the Line/Hot (L/H) terminal on the driver, it is preferred not to use the switched hot (red) wire from the control but rather the hot wire directly from the power source.
- Recommended for EasySense System.


NRC COMPARISON

Frequency/Hz	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	ā	NRC
0mm / 0"	0.03	0.01	0.09	0.04	0.05	0.09	0.12	0.25	0.32	0.49	0.61	0.72	0.82	0.85	0.91	0.94	0.95	0.44	0.45
50mm / 2"	0.20	0.16	0.22	0.32	0.46	0.56	0.63	0.80	0.89	1.03	1.04	0.99	1.07	1.00	0.93	0.87	0.92	0.81	0.80
150mm / 6"	0.29	0.46	0.44	0.57	0.68	0.81	0.97	0.96	0.91	1.04	0.92	0.80	0.94	0.94	0.91	0.90	0.91	0.97	0.90




CUBE2-NRC-X

<STANDARD>




SL: SLATE




PW: PEWTER


<PREMIUM>




TR: TAR




MD: MANDARIN




OC: OCHRE




GR: GRASS




SS: SUNSHINE




FR: FROST



IV: IVORY




LN: LINEN




EC: ECRU




BR: BARK




CH: CHAMBARY




SK: SKY




CB: COBALT




FO: FOSSIL




GE: GREIGE



CD: CADET



MC: MALACHITE



SM: SMOKE

1. Standard finish is free of charge.
2. Premium finish with extra charge. Please contact factory for more information.

CUBE2-NRC-X LIT CONNECTOR PATTERNS

The lit connector system allows continuous illumination all the way through the corner section.

- Instruction:**
- Please provide sketches illustrating corner types, overall dimensions including corner dimensions, and locations required.
 - HC90, TC, and XC connectors are 90 degree corners (overall, outside dimension).

A large grid for sketching connector patterns, with the UTOPIA LIGHTING logo centered at the top. The grid is composed of 30 columns and 30 rows of squares. The logo is centered horizontally and vertically within the top 10 rows of the grid.