

FLPL50-F-2G

Project Name:	
Type:	



FEATURES:

- Aluminum housing with frame.
- Non-toxic, non-radioactive, and recyclable aluminum.
- 50 feet viewing distance.
- Aluminum panel background with photoluminescent yellowish surface printed letter available in Red, Green, or Black panel.
- Single or double sided (two same-colored side panels).
- Two self-adhesive chevron stickers are included in case the directional chevron(s) is required.
- Need at least 5 foot candle of fluorescent illumination on the face of the sign at all times.

MOUNTING:

- Accessories for flat wall mount included as standard.
- Optional: ceiling or perpendicular (side wall) flag mount.

LISTING:

- Listed to Standard UL924 by ETL Intertek Testing.
- IBC and IFC codes compliant.
- OSHA and NFPA 101-Life Safety Code compliant.
- Listed for high-location and floor-proximity installation, impact resistant.

Specifications: FLPL50-F-2G

Tall: 10-1/4 (260)
 Wide: 18-3/4 (476)

All dimensions are in inches (millimeters).



1.5B : 1.5" away from Ceiling or Side wall.
 10B : 10" away from the Ceiling.
 19.5B : 19.5" away from the Ceiling.

ORDERING INFORMATION

EXAMPLE: FLPL50-F-2G-S-R

MODEL	# OF FACE	PANEL COLOR	MOUNTING BRACKET	
FLPL50-F-2G	S Single D Double ¹	R Red panel with yellow letter G Green panel with yellow letter B Black panel with yellow letter	1.5B 10B 19.5B	Mounting bracket 1.5" away from ceiling or side wall (flag mount) Extended mounting bracket 10" away from ceiling mount Extended mounting bracket 19.5" away from ceiling mount

NOTES:

1. Two same-colored side panels.