

TCEX

Project Name:	
Type:	



APPLICATION

Ideal for commercial where economy, appearance and the ultimate ease of installation and maintenance are desired. Solid-state electronics offer both reliability and low-cost performance.

FEATURES:

- Thin Thermoplastic LED Exit Sign Compact size low-profile design LED exit sign.
- Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Innovative snap-together design allows for fast and easy installation.
- Letters 6" height with 3/4" stroke.
- Easily removable snap-out knockouts and chevron directional arrows.
- 90+ minute emergency operation.
- Available in white or black housing.

MOUNTING:

- Mounting canopy included for top or end mount.

ELECTRICAL:

- 120/277V dual voltage operation standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

LAMPS:


- Ultra-bright, energy efficient, long-life Red or Green LEDs with more than 10 year lifecycle.
- LEDs have a minimum rated lamp life of 100,000 hours.

BATTERY:

- Long-life, maintenance-free, rechargeable NiCd battery on emergency (EM) units.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Internal solid-state transfer switch automatically connects the internal battery to LEDs for minimum 90 minute emergency illumination.

LISTING:

- 5 years limited warranty on materials and all electronics. Battery prorated for five years.
- LED lamps are 25 years limited warranty.
- UL listed for damp locations.
(32°F ~ 122°F / 0° ~ 50°C)
- Meets UL924, NFPA 70, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- 5VA Flame Retardant.
- ARRA compliant. (optional)



All dimensions are in inches (millimeters).

ELECTRICAL INFORMATION

	Input Watts (W)	Input Amps (A)
Red / Green	120V	1.0W
	277V	1.0W
	0.010A	0.010A

ORDERING INFORMATION

EXAMPLE: TCEX-S-R-1-WH

MODEL	# OF FACE	LETTER	OPERATION	HOUSING COLOR	OPTIONS					
TCEX	S D	Single Double	R G	Red Green	(Blank) 1	AC-only Battery Back up	WH BK	White Face / White Housing Black Face / Black Housing	WG-1 PCS-1 BG-1 ARRA	Steel Wire Guard (13.5" x 15" x 6") Polycarbonate Guard (3.25" x 9" x 2.75") Polycarbonate Vandal Shield Guard (15" x 22" x 8") Assembled in USA for ARRA and BAA compliant