

RSHL-2G-C



CASambi

APPLICATION

Family of direct and indirect luminaires component high reflectance. Recessed fixture with slope high transmission diffuser panels manage contrast and generate soft even higher angle luminance. Ideal for hospitals, hallway, conference rooms, offices, schools and other numerous other commercial applications.

FEATURES:

- Architectural low-profile design, shallow direct/indirect housing, 22-gauge die formed C.R.S steel galvanized housing with high reflectance.
- Non-glare white powder coat finish over rust inhibiting phosphate coat.
- Shallow recessed luminaires, available in dual enclosed lens configurations.
- 86% minimum average reflective white powder coat housing.
- Lens to be white translucent polycarbonate engineered optical uniformity. Tool-free removable.
- Reflectors and shields in white powder coated finish.
- PAF (Painted After Fabrication) finish is standard for corrosion resistance and efficiency.

MOUNTING:

- Recessed mount in expose T-bar ceilings, Internal T-bar safety clips.
- Field installed flange kits are available.
- Compatible with most ceiling types.

LED:

- Field adjustable color temperature: 3000/3500/4000/5000(K)
- LED Module: High efficiency up to 134 LPW.
- Service life: Greater than 54,000 hours(L_{70}) minimizing maintenance frequency.
- Poke in wire connectors.
- Color variation within 3-step MacAdam ellipse.

ELECTRICAL:

- High power factor electronic driver, operate from a 108 ~ 305 Vac input range, 50 / 60 Hz.
- Features included over voltage protection, surge, short circuit protection and over load protection.
- Power Factor: typical > 0.90
- Class 2 and SELV
- 0-10V dimmable driver as standard.
- To find an approved dimmer switch, please see table 1.
- Ambient Operating Temperature: -4°F (-20°C) ~ 122°F (50°C).
- <ELCU-200>
- Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
- Interfaces with fire alarm panel or security system.
- "Watchdog" feature allows emergency loads to be controlled in tandem with normal power loads.
- UL listed for use in emergency circuits.

LISTING:

- ROHS.
- ETL listed.
- DLC premium listed.²
- CEC Compliant EM (please contact for more information)
- Recessed Luminaires, Type IC
- Suitable for damp locations.
- 5 year warranty.
- ARRA compliant (optional).
- BAA compliant (optional).
- Trade Agreements Act compliant (optional).

CONFIGURATIONS


	Size	LED Watts	Lumen Output	Color Temp.	Lumen Efficiency
RSHL-2G	2' x 2'	20W, 25W, 30W, 35W, 40W	2680 lm, 3350 lm, 4020 lm, 4690 lm, 5360 lm	4000K	134 lm/W
	2' x 4'	25W, 30W, 35W, 40W, 50W	3350 lm, 4020 lm, 4690 lm, 5360 lm, 6700 lm		134 lm/W

: Based on 4000K.

Multiplier		
3000K	3500K	5000K
0.9502	0.9837	1.0173

LED RECESSED SHALLOW BASKET LENS

RSHL-2G-C



Specifications: 2'x2'


Length: 23.74 (603)
Width: 23.74 (603)
Depth: 1.8 (45)

Specifications: 2'x4'

Length: 48 (1218)
Width: 23.74 (603)
Depth: 1.8 (45)

All dimensions are in inches (millimeters).

Field selectable access on the back



RSHL-2G-C

ORDERING INFORMATION

EXAMPLE: RSHL-2G-22-C-5S-4T-UNV-DM

MODEL	SIZE		SHIELD		LED		COLOR TEMP.		CRI		
RSHL-2G	22	2' x 2'	C	Center	5S	20W /25W /30W /35W /40W LED	4T	Selectable 30/35/40/50K	(Blank)	80+ CRI	
	24	2' x 4'			5S	25W /30W /35W /40W /50W LED	4T	Selectable 30/35/40/50K			
MOUNTING		DIFFUSER		VOLTAGE		LED DRIVER		PRESET			
(Blank) FK SMK	Grid Flange Kit (Field Install) ¹ Surface Mount Kit	(Blank)	White opal polycarbonate diffuser	UNV	120-277V	DM	Dimming Ballast 10~100% dim (Std.)	(Blank) PS(Lxx,yyK)	Non-Preset Preset Request; XX for watt, YY for CCT		
OPTIONS					LIGHTING CONTROL SYSTEM						
EMI15 EMI25 ELCU-200 GTD GTD10DIM ARRA BAA TAA O7W O10W AMB HC403	2430 LUMEN EM Battery Backup (CEC Compliant EM) ³ 4050 LUMEN EM Battery Backup (CEC Compliant EM) ³ Fail-to-on Emergency lighting, UL924 ⁶ Bodine Generator Transfer Device Bodine Generator Transfer Device (0-10VDC Dimmer Override) Assembled in USA for Buy American act BAA(Buy American Act) and BABA(Build America Buy America) compliant Trade Agreements Act compliant Optional 7 Years Limited Warranty ^{5,7} Optional 10 Years Limited Warranty ^{5,7} Anti-Microbial Coating (Matte Skye White) Integrated Microwave bi-level Occupancy Sensor	PPA102S	<Bluetooth> Bluetooth Powerpack (Consult factory for installation location)								
			CASAMBI	Contact factory for CASAMBI READY options							

NOTES:

1. Flange kits are supplied in separate boxes, field installed.
2. DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified.
Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.
3. Contact factory for other emergency ballast options.
4. Custom wattage products are not DLC qualified.
5. This limited warranty covers electrical parts only and does not apply to labor, equipment lease, or defect from improper installation or operation. (EM battery backup does not included)
6. Shipped separately.
7. Only available with fixed wattage and CCT.

COMPATIBLE DIMMER SWITCH (TABLE 1)

Model #	Brand	Compatible Dimmer Switch		
(Blank)	-	<Leviton>	IllumaTech IP7 series	
		<Lutron>	Visit www.lutron.com/advance for a list of dimmers (Mark VII) that will work with this driver.	
		<Philips>	Sunrise : SR1200ZTUNV	