

BLD4

Project Name:	
Type:	



CASAMBI

APPLICATION

LED bollard light provide high light efficiency. Energy saving replacement of Metal Halide and High pressure sodium lamps with a driver inside. It is designed to work in building perimeter areas and public spaces completing a wide variety of architectural styles.

FEATURES:

- Die-cast extruded aluminum housing
- Round appearance for good decorative effect, sized in 3.5ft height.
- Dark bronze polyester powder-coat finish.
- Robust ground cage pre-buried installation.
- Operating temperature: -40°C to 40°C (-40°F to 113°F)
- Field adjustable wattage and color temperature.

MOUNTING:

- Ground mount.
- Template and anchor bolt are provided.

LED:

- Lumileds 3030.
- 26/21/16/10W selectable.
- Field adjustable Color Temperature: 3000 / 4000 / 5000K
- Color rendering index: >80
- Life span: >50,000 hours
- 360° distribution
- Lumen Maintenance L70 greater than 100,000 hours IESNA TM-21.

ELECTRICAL:

- Input voltage: 100-277Vac., 50/60Hz
- 1-10V dimming standard.

OPTIC:

- Clear diffuser is standard.

LISTING:

- UL/cUL listed.
- Wet location listed.
- DLC premium listed.
- ARRA compliant. (optional)

CONFIGURATIONS

Series	System Watts	Lumen Output	Lumen Efficiency
BLD4	26W	3200 lm	123 lm/W
	21W	2700 lm	128 lm/W
	16W	2100 lm	131 lm/W
	10W	1400 lm	140 lm/W

ORDERING INFORMATION

EXAMPLE: BLD4-26LED-3T-UNV-D-C

MODEL	LED	COLOR TEMP.	VOLTAGE	FINISH	DIFFUSER
BLD4	26LED	26/21/16/10W selectable LED	3T	Selectable 30/40/50K	UNV 120-277V

OPTIONS		LIGHTING CONTROL SYSTEM	
EMG8W PC ARRA	8W EM Battery Backup Photocell Assembled in USA for Buy American act	LRF-INT CASAMBI	<Lutron Vive System Enabled> Limelight by Lutron Radio Module PCB Assembly Contact factory for CASAMBI READY options

BLD4

