

MFL7-2G LED

Project Name:

Type:



APPLICATION

The MFL7-2G luminaire is a high performance LED lighting solution designed with optical versatility and a slim, low profile design. Its rugged cast aluminum housing minimizes wind load requirements and features an integral, watertight power source compartment and high performance aluminum heat sinks. Suitable for parking lots, walkways, car dealerships, roadways, and etc.

FEATURES:

- Solid construction die-cast aluminum housing.
- Die-cast aluminum heat sink providing the most ideal heat dissipation.
- UV stabilized powder coated finish.
- Field adjustable color temperature.
- On/off switchable photocell included as standard.
- Comes with 6" cord as standard.

MOUNTING:

- Knuckle mount (1/2" NPS).
- Trunnion mount.
- Slip Fitter.

LED:

- Field adjustable Color Temperature: 3000/4000/5000K
- Lumen efficiency: up to 136 lm/W
- Color rendering index > 80
- L70: > 54,000 hrs

LENS:

- Diffuse PC lens to provide efficient distribution.
- NEMA 7X7 distribution.

ELECTRICAL:

- Input Voltage: 120-277VAC, 50-60Hz
- 0-10V dimming standard.
- Power Factor: >90%
- THD <20%
- Operating temperature: -40°F~104°F (-40°C~40°C)

LISTING:

- UL / cUL listed.
- DLC qualified.
- Suitable for wet location.
- 5 years limited warranty.
- BAA compliant (optional).

SPECIFICATION

	Model#	AC Input	Lumen Output (3000K)	Lumen Efficiency (3000K)	Lumen Output (4000K)	Lumen Efficiency (4000K)	Lumen Output (5000K)	Lumen Efficiency (5000K)
MFL7-2G	15LED	13.8W	1783 lm	129.4 lm/W	1806 lm	142.1 lm/W	1902 lm	136.4 lm/W
	25LED	23.8W	3076 lm	129.4 lm/W	3228 lm	142.1 lm/W	3266 lm	136.4 lm/W
	36LED	34.8W	4499 lm	129.4 lm/W	4791 lm	142.1 lm/W	4767 lm	136.4 lm/W
	50LED	46.1W	5867 lm	127.3 lm/W	6232 lm	141.3 lm/W	6212 lm	131.3 lm/W
	70LED	66.1W	8412 lm	127.3 lm/W	9059 lm	141.3 lm/W	8837 lm	131.3 lm/W
	90LED	86.1W	10957 lm	127.3 lm/W	11885 lm	141.3 lm/W	11463 lm	131.3 lm/W
	105LED	106.6W	13741 lm	128.9 lm/W	14376 lm	142.2 lm/W	14187 lm	132.2 lm/W
	120LED	121.6W	15675 lm	128.9 lm/W	16509 lm	142.2 lm/W	16170 lm	132.2 lm/W
	150LED	151.6W	19541 lm	128.9 lm/W	20775 lm	142.2 lm/W	20137 lm	132.2 lm/W

MFL7-2G LED

ORDERING INFORMATION

EXAMPLE: MFL7-2G-3SM-3T-UNV-BZ-TR

MODEL	LED	COLOR TEMP.	VOLTAGE	DRIVER	FINISH
MFL7-2G	3SL 3SM 3SH	30/20/10W Selectable LED 90/70/50W Selectable LED 150/120/105W Selectable LED	3T Selectable 30/40/50K	UNV 120-277V	(Blank) 0-10V dimming (Std.)
					BZ WH *CC Dark Bronze RAL#7022 (Std.) White, Cardinal #WH04 Custom Color * Available custom color (RAL) Please provide us with the RAL number. * Non-standard finish with extra charge.

MOUNTING ¹	PHOTOCELL	OPTIONS
KN TR SF Knuckle Mount Trunnion Mount Slip Fitter	(Blank) On/off switchable photocell (std.)	SP4 SP10 BAA BABA WG VL MG 4Kv surge protector Integrated 10kV/10kA surge protection BAA(Buy American Act) compliant BABA(Build America Buy America) compliant ² Wireguard Vandal Lens Shield Marine Grade Finish

NOTES:


- 3SL & 3SM: only available with KN and TR mount.
3SH: only available with SF and TR mount.
- Not all configurations may comply. Please confirm compliance with the factory.



Easy access to the control switch for a range of CCTs and wattages to choose from.



Easy access to photocell switch. Photocell is replaceable.



WG (optional)




VL (optional)

MFL7-2G LED


All dimensions are in inches (millimeters).

3SL




TR

3SM




TR

3SH



SF



TR