

## REM

**FEATURES:**

- Injection-molded, engineering grade, 5VA flame retardant, impact-resistant, thermoplastic in off white or black finish.
- Injection-molded, engineering grade, 5VA flame retardant, thermoplastic oval and rectangle trim plates in off white or black finish included.

**ILLUMINATION:**

- Ultra-bright, energy efficient, long-life white LED lamp heads.
- 1.0 watt (1 LED x 1.0 watt) per head.
- Unique all-inclusive lamp, reflector, and lens assembly.
- Adjustable LED lamp heads provide up to 50-ft center-to-center spacing with a 3-ft path of egress at 12-ft mounting height.

**MOUNTING:**

- Bar hangers included are compatible with drywall or drop ceiling mount installations.

**FUNCTION:**


- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

**ELECTRICAL:**

- Universal 120-277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable nickel metal hydride battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**LISTING:**

- Five-year warranty on all electronics and housing. Battery pro rated for five years.
- UL Listed for damp locations (10°C – 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.



All dimensions are in inches (millimeters).

**ORDERING INFORMATION****EXAMPLE: REM-W-SDT**

| MODEL | FINISH                 | OPTIONS |                  |
|-------|------------------------|---------|------------------|
| REM   | W Off White<br>B Black | SDT     | Self-Diagnostics |