

W LED



CASambi

APPLICATION

Specification grade surface ceiling-mount standard wraparound fixture delivers diffuse moderate light. It is the economical, energy-efficient, high performance and low-profile choice for small to medium size offices, retail spaces, classrooms and storage rooms.

FEATURES:

- 0.08" thk 100% acrylic, injection molded prismatic basket diffuser with flat bottom and vertical sides.
- Die formed, cold-rolled, heavy gauge steel housing construction provides durability and strength.
- End caps are same material as housing.
- Lens are capable of being hinged from either side for easy cleaning and service.
- Finish is high-gloss baked white enamel over rust inhibiting phosphate coating for maximum corrosion resistance.
- Paint after fabrication.
- 5% uplight.

MOUNTING:

- Surface mount.
- Stem mount (1/2" std, 3/8" optional) (pipe by others unless ordered).
- Steel end plates with 7/8" KO standard for continuous row mounting option.
- Compatible with most ceiling types.

LED:

- High quality array LEDs.
- LM80
- Color Temperature: 2700/3000/3500/4000/5000 (K)
- Color Rendering Index: > 82.8
- Calculated L70: 122,000 hours
- Reported L70: +60,000 hours

ELECTRICAL:

- High power factor electronic driver, operate from a 120 ~ 277 Vac input range, 50 / 60 Hz.
- Features included over voltage protection, surge, short circuit protection and over load protection.
- Power Factor: typical > 0.95, THD <20, meets Class1 or Class 2 circuit.
- Generic : 0-10V 10% dim. (GR)
- Operating temperature: -4°F (-20°C) ~ 122°F (50°C).
- <ELCU-200>
- Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
- Interfaces with fire alarm panel or security system.
- "Watchdog" feature allows emergency loads to be controlled in tandem with normal power loads.
- UL listed for use in emergency circuits.

LISTING:

- UL/CUL listed.
- Listed to UL 1598 and UL 8750.
- DLC listed.²
- Suitable for damp locations.
- CEC Compliant EM (please contact for more information)
- Optional ARRA compliant.
- BAA compliant (optional).
- Trade Agreements Act compliant (optional).
- 5 years limited warranty.
- 7 or 10 years limited warranty. (optional)³
- Bluetooth Mesh System available, please contact factory for more information.

CONFIGURATIONS

Series	Size	LED Watts	AC Input	Lumen Output	Driver Input
W	2FT	18LED	19.8W	2126.52 lm	277V
		25LED	27.5W	2953.5 lm	
		36LED	39.6W	4253.04 lm	
	4FT	18LED	19.8W	2126.52 lm	
		25LED	27.5W	2953.5 lm	
		36LED	39.6W	4253.04 lm	
		54LED	59.4W	6379.56 lm	
	8FT	72LED	79.2W	8506.08 lm	
		54LED	59.4W	6379.56 lm	
		72LED	79.2W	8506.08 lm	
		108LED	118.8W	12759.12 lm	


: Based on 3500K.

OUTPUT CURRENT

		Bi-Level		Tri-Level (Default)	
SW1	SW2	Config Range	Default	Config Range	Default
Close	Open	10% - 70%	40%	10% - 70%	30%
Open	Close	10% - 70%	40%	10% - 70%	70%
Close	Close	100%	100%	100%	100%
Open	Open	0%	0%	0%	0%

MULTIPLIER CHART

CCT	Multiplier		
	3000K	4000K	5000K
2FT	0.958	1.0112	1.0214
4FT	0.988	1.0122	1.0245
8FT	0.989	1.0122	1.0235



Specifications: W-2

Weight: 7.56 lbs (3.43 kg)

Specifications: W-4

Weight: 11.97 lbs (5.43 kg)

Specifications: W-8

Weight: 19.69 lbs (8.93 kg)

LED WRAPAROUND

ORDERING INFORMATION

EXAMPLE: W-4-2G-36LED-40K-UNV-SD50

MODEL	LENGTH	GENERATION	LED	COLOR TEMP.	EFFICACY	CRI	
W	2' Length 4' Length 8' Length ¹⁰	2G	2ND Generation	18LED 18W LED 25LED 25W LED ⁴ 36LED 36W LED 54LED 54W LED 72LED 72W LED 108LED 108W LED	-27K 2700K ⁶ -30K 3000K -35K 3500K -40K 4000K (Std.) -50K 5000K	(Blank) HE Standard High Efficacy ^{10%}	(Blank) C9 80+ CRI 90+ CRI ⁷

^{*} Contact factory for custom wattage or lumen requirement.

DIFFUSER		VOLTAGE		LED DRIVER		
(Blank) SG8	Acrylic Lens 1-piece 8FT lens for W-8	UNV 120 277 347	120-277V (Std.) 120V 277V 347V	GR DM SD40 SDXX TD30/70 TDXX/YY ES566 EC LDE1 ELV PHSR PHDL TDM ED560 LTEA2W	Generic, 0-10V 10% dim (Std.) ⁴ Generic 0-10V 1% dim 40% / 100% Bi-Level Step dim XX% / 100% Bi-Level Step dim (Specify XX : 10% ~ 70%) 30% / 70% / 100% Tri-Level Step dim XX% / YY% / 100% Tri-Level Step dim (Specify XX, YY : 10% ~ 70%) eldoLED SOLOdrive Natural Dimming to dark, 0-10V, 100% ~ 0.1% dim eldoLED ECODrive 0-10V natural dim to 1% (Hybrid HydraDrive) Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology, 100% ~ 1% dim ELV compatible (reverse-phase or trailing-edge), (120V only) Philips Xitanium Sensor-Ready, Dali 5%~100% dim Philips Xitanium DALI driver, Dim to 5% Triac Dim. (120V only) eldoLED LightShape DALI dim to dark, 0.1% ~ 100% Hi-lume 1% 2-wire LED driver (120V forward phase only)	 BLT Bluetooth Mesh System (contact factory for more information)

MOUNTING		OPTIONS			LIGHTING CONTROL SYSTEM	
(Blank) ACxx	Ceiling Mount Adjustable Aircraft Cable w/ Canopy (* xx = Specify length (48 or 96))	EMG8 EMG15 EMG20 EMG26 ELCU-200 GTD GTD10DIM ARRA BAA	1296 LUMEN EM Battery Backup (CEC Compliant EM) ¹ 2430 LUMEN EM Battery Backup (CEC Compliant EM) ¹ 3240 LUMEN EM Battery Backup (CEC Compliant EM) ¹ 4050 LUMEN EM Battery Backup (CEC Compliant EM) ¹ Fail-to-on Emergency lighting, UL924 ⁸ Bodine Generator Transfer Device Bodine Generator Transfer Device (0-10VDC Dimmer Override)	LUTRON VIVE	<Lutron Vive System Enabled>  Click Here!	
YCxx	Adjustable Aircraft Y-cable with Toggles (* xx = Specify length in inches (60, 120, 180))	TAA O7W O10W LOD-500S	Assembled in USA for Buy American Act BAA(Buy American Act) and BABA(Build America Buy America) compliant Trade Agreements Act compliant Optional 7 Years Limited Warranty ³ Optional 10 Years Limited Warranty ³	PPA102S	<Bluetooth> Bluetooth Powerpack (Consult factory for installation location)	
SH-1/2-xx	1/2" IPS STEM w/ Canopy (* xx = 18, 24, 36, 48 inches)	RS-LRD LRD-509S-x	Fixture external mounted Bi-level 0-10V occupancy sensor with standard cone shape 8-15ft mounting height with coverage of 2X height, with DIP switch setting ⁹ Remote programmer for LRD-509S and LRS-50 9S	CASAMBI	Contact factory for CASAMBI READY options	
SH-3/8-xx	3/8" IPS STEM w/ Canopy (* xx = 18, 24, 36, 48 inches)	AMB HC403	Fixture external mount 0-10V SmartDIM or multi-level high/low dim control occupancy sensor (*IR remote programmable), (See note 12 to select lens for "x") ^{9, 11} Anti-Microbial Coating (Matte Skye White) Microwave bi-level Occupancy Sensor, adjustable via DIP switch ¹³			

NOTES:

1. Contact factory for other emergency ballast options. Must specify voltage, not available with 347V.
2. DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified.
Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.
3. This limited warranty covers electrical parts only and does not apply to labor, equipment lease, or defect from improper installation or operation. (EM battery backup does not included)
4. To find an approved dimmer switch, please see table 1.
5. Not available with GR driver.
6. Available with C9 only.
7. Lumen per watt is around 15% less than standard CRI (80+).
8. Shipped separately.
9. Its default setting can be found on the IR-TEC installation instructions.
10. Two 4ft lenses come as standard. Must choose the SG8 option for one 8ft lens.
11. Order "RS-LRD" to adjust sensor setting.
12. A: Standard cone shape Lens @ 15' height (up to 30' coverage)
B: Extra wide cone shape Lens @ 10' height (up to 60' coverage)
C: High bay cone shape Lens @ 30' height (up to 90' coverage)
D: Standard round shape Lens @ 20' height (up to 40' coverage)
F: Extra wide dome shape Lens @ 20' height (up to 80' coverage)
G: Aisle way arch shape Lens @ 40' height (up to 120' coverage)
13. See Table2 to find factory setting.

COMPATIBLE DIMMER SWITCH (TABLE 1)

Model #	Brand	Compatible Dimmer Switch	
(Blank)	-	<Leviton>	IllumaTech IP7 series
		<Lutron>	Visit www.lutron.com/advance for a list of dimmers (Mark VII) that will work with this driver.
		<Philips>	Sunrise : SR1200ZTUVN
ES566	eldoLED SOLOdrive	<Busch-Jaeger>	2112U-101
		<Jung>	240-10
		<Leviton>	IllumaTech - IP710-DLX
		<Lightoller Controls>	ZP600FAM120
		<Merten>	5729
		<Pass & Seymour>	CD4FB-W
		<Wattstopper>	DCLV1
		<Sensor Switch>	nI/O EZ
		<Synergy>	ISD BC
		<ABB>	SD/S 2.16.1
		<Lutron>	Nova T: NTFTV Diva - DVTV-xx, NFTV GRAFIK Eye: GRX-TVI w GRX3503 Energy Savr Node: QSN-4T16-S TVM2 Module
		<Crestron>	GLX-DIMFLV8, GLXP-DIMFLV8, GLPAC-DIMFLV4-*, GLPAC-DIMFLV8-*, GLPP-DIMFLVEX-PM, GLPP-1DIMFLV2EX-PM, GLPP-1DIMFLV3EX-PM, DIN-A08, DIN-4DIMFLV4, CLS-EXP-DIMFLV, CLCI-1DIMFLV2EX
LDE1	Lutron 5-Series EcoSystem	<Lutron>	PowPak Dimming Modules: RMJ-ECO32-DV-B, FCJ/FCJS-ECO ^{1,2} Energi Savr Node (120V only): QSN-1ECO-S, QSN-2ECO-S GRAFIK Eye QS/Homeworks QS control unit (120V only): QSGRJ- <u>E</u> (wireless) QSGR- <u>E</u> Quantum Hub (120V only): QP2- <u>2</u> 2C/4C/6C/8C Homeworks QS/myRoom Plus power module (120V only): LQSE-2ECO-D
LTEA2W	Lutron Hi-lume 2-wire (120V forward voltage only)	<Lutron>	Visit http://www.lutron.com/TechnicalDocumentLibrary/369543_ENG.pdf for a list of compatible dimmer switches.
TDM	KEYSTONE	<Lutron>	Diva DV-600P, SkyLark S-600P, Ariadni AY-600P, Ariadni TG-603P, Maestro MA-600 (Digital), Diva CFL/LED DVCL-153P, Satin Colors DVSC-600P-SW
		<Leviton>	6641, IllumaTech IPI06-1LX, ToggleTouch TGI06-1LW (Digital)
ELV	KEYSTONE	<Lutron>	MAELV-600BL (Digital), DVELV-300P, SkyLark SELV-300P

NOTES:

- All devices connected to one FCJ/FCJS-ECO will be controlled together. Devices will dim to the same level as the result of a control command.
For more detail on adjusting low-end light level refer to Application Note#556 at www.lutron.com.
- For the Line/Hot (L/H) terminal on the driver, it is preferred not to use the switched hot (red) wire from the control but rather the hot wire directly from the power source.


HC403 FACTORY SETTING (TABLE 2)

Detection Area	100%
Hold-time	5 sec
Daylight sensor	Disable
Stand-by period (tri-level control)	10 sec
Stand-by dimming level	10%


* See a separate attachment to find more setting options.

LED WRAPAROUND







2FT



4FT




8FT



W LED


W-2-18LED




W-2-25LED




W-2-36LED



W-4-54LED



W-4-72LED



W-8-108LED

